



Dimensionen: Blistergurt und Rolle

gemäss IEC 60286-3

Typ	P1	F	W	N	W1	W2	A	A	A	A	A	A	A	A	A	
	[mm]	[mm]	[mm]	[mm]	[mm]	[mm]	500 St.	750 St.	1000 St.	1500 St.	2000 St.	3000 St.	5000 St.	6000 St.	10000 St.	15000 St.
							[mm]	[mm]	[mm]	[mm]	[mm]	[mm]	[mm]	[mm]	[mm]	[mm]
USF 0402	2	3.5	8	62	8.4	14.4										180
USF 0603	4	3.5	8	62	8.4	14.4			180				254			330
USFF 1206	4	3.5	8	62	8.4	14.4			180				254		330	
USF 1206	4	3.5	8	62	8.4	14.4			180				254			330
USI 1206	4	3.5	8	62	8.4	14.4			180				254			330
UST 1206	4	3.5	8	62	8.4	14.4			180				254			330
MGA	4	3.5	8	62	8.4	14.4		180				330				330
MGA-S	4	3.5	8	62	8.4	14.4										
UMF 250	8	11.5	24	62	24.4	30.4					330					
UMZ 250	8	11.5	24	62	24.4	30.4			330							
UMT 250	8	11.5	24	62	24.4	30.4					330					
UMK 250	8	11.5	24	62	24.4	30.4			330							
UMT-H	8	11.5	24	62	24.4	30.4				330						
172876	4	5.5	16	62	16.4	20.4				180						
MKF	4	5.5	12	62	12.4	18.4	180			180						
MSB	4	5.5	16	62	16.4	20.4				180						
MKT	4	5.5	12	62	12.4	18.4	180			180						
OMF 63	8	7.5	16	62	16.4	22.4		180				330				
OMK 63	8	11.5	24	62	24.4	30.4				330						
OMF 125	8	7.5	16	62	16.4	22.4		180				330				
OMK 125	8	11.5	24	62	24.4	30.4		180		330						
OMT 125	8	7.5	16	62	16.4	22.4		180				330				
OMZ 125	8	11.5	24	62	24.4	30.4		180		330						
OMF 250	8	11.5	24	62	24.4	30.4				330						
OMT	8	11.5	24	62	24.4	30.4				330						
TF 600	8	11.5	24	62	24.4	30.4				330						
OSU 125	8	7.5	16	62	16.4	22.4		180				330				
OSU 250	8	11.5	24	62	24.4	30.4				330						
OMH 125	8	11.5	24	62	24.4	30.4		180		330						
PFNF	4	3.5	8	62	8.4	14.4						180				
PFUF	4	3.5	8	62	8.4	14.4						180				
PFMF	8	5.5	12	62	12.4	18.4			180	180						
PFDF	8	7.5	16	62	16.4	22.4								360		
PFSM	8/12	7.5	16	62	16.4	22.4			360	360						
PFHT	8/12	7.5	16	62	16.4	22.4			360	360						