





















Product overview








Connectors & power entry modules

Connector type	Extras	IEC connector type							Features						Mounting					Connection							
		Inlet	Outlet	Protection class I	Protection class II	Max. pin temperature [°C]	V-Lock cord retaining	Enhanced glow wire	Fuseholder 1-pole	Fuseholder 2-pole	Switch 1-pole	Switch 2-pole	Switch illuminated	Circuit breaker	Voltage selector	Components prewired	Screw-on front	Screw-on rear	Snap-in	Drop-in	Sandwich	Quick connect	Solder terminals	Screw terminals	PCB	IDC terminals	Alternate type with line filter
IEC 2.5 A / UL 2.5 / 7 A																											
	0720-FS 0720-FP	•		C8	70											•	•					•					
	0721-PS 0721-PP	•		C8	70												•					•					
	2576 2578	•		C8	70											•					•	•				5008	
	2570	•		C8	70															•	•						
	2577 2579	Polarized Polarized	•	C8p	70											•					•	•				5008	
	0724		•	C6	70											•	•					•					
	2563	Retaining bracket	•	C6	70																•	•					
	2565		•	C6	70																•	•					
	5082	For docking systems	•	D	70											•						•					
	5084 5086		•	D	70											•						•					
	5083		•	D	70																	•					
	5088		•	D	70											•						•					
	CMF1 CMF2 CMF3	Polarized	•	C8	70					•						•											
			•	C8p	70					•						•											
			•	C6	70					•						•											
IEC 10 A / UL 15 A																											
	6100-3 6100-4	IP 54 opt.	•	C14	70	•										•	•				•	•				5120 5110	
	6102-3 6102-5		•	C18	70	•										•	•				•	•				5120	

Connector type	Extras	IEC connector type						Features						Mounting					Connection																				
		Inlet	Outlet	Protection class I	Protection class II	Max. pin temperature [°C]	V-Lock cord retaining	Enhanced glow wire	Fuseholder 1-pole	Fuseholder 2-pole	Switch 1-pole	Switch 2-pole	Switch illuminated	Circuit breaker	Voltage selector	Components prewired	Screw-on front	Screw-on rear	Snap-in	Drop-in	Sandwich	Quick connect	Solder terminals	Screw terminals	PCB	IDC terminals	Alternate type with line filter												
IEC 10 A / UL 15 A																																							
	6150	•		C14		70												•																					
	1061	•		C14	C18	70												•																					
	6010 6015	•		C14		70	•											•																					
	6048	•		C14		70	•											•	•																				
	6061 6061-G	•		C14	C18	70	•											•																					
			Gold plated contacts															•																					
	6130-56	•		C14		70	•											•																					
	GSP1	•		C14	C18	70	•											•																					
	GSP2	•		C14	C18	70	•	•										•	•	•	•																		
	4761		IP 67		Spez													•																					
	new																																						
	6110-3 6110-4	•		C16		120	•											•	•																				
		•		C16		120	•												•																				
	6120-3 6120-5	•		C16A		155												•	•																				
		•		C16A		155													•																				
	DC11	•		C14	C18	70	•	•		•	•	•			•			•	•	•																			
	DC21	•		C14		70	•				•	•			•			•																					
	KEB1	•		C14		70				•					•			•	•	•																			
	KEB2	•		C14		70					•	•			•			•	•	•																			
	6135	•		C14		70	•				•	•	•		•			•																					
	6145	•		C14	C18	70					•	•	•		•			•																					
	DF11	•		C14		70	•				•	•	•		•			•	•	•																			

Connector type	Extras	IEC connector type							Features							Mounting					Connection						
		Inlet	Outlet	Protection class I	Protection class II	Max. pin temperature [°C]	V-Lock cord retaining	Enhanced glow wire	Fuseholder 1-pole	Fuseholder 2-pole	Switch 1-pole	Switch 2-pole	Switch illuminated	Circuit breaker	Voltage selector	Components prewired	Screw-on front	Screw-on rear	Snap-in	Drop-in	Sandwich	Quick connect	Solder terminals	Screw terminals	PCB	IDC terminals	Alternate type with line filter
IEC 10 A / UL 15 A																											
	6610	Cross & along versions	•	F	70	•												•								•	
	6650		•	F	70													•								•	
	4721 4723	Shuttered Shuttered	• •	F F	70 70													•			•	•					
	4787 4788		• •	F F	70 70													•			•	•					
	5091		•	F	H 70													•			•	•			•		
	5001		•	F	H 70													•							•		
	4719	Shuttered, neon indication	•	F	70		•											•			•						
IEC 16 A / UL 20 A																											
	4798 4793		• •	C20 C20 C24	70 70	• •												•			•	•					5130 C20F
	GSP4		•	C20 C24	70	•	•											•	•	•	•				•		
	1681		•	C22	155	•												•	•		•	•	•				C22F
	EC11		•	C20 C24	70	•	•		•	•	•			•	•	•	•				•						EC12
	6136		•	C20	70	•			•	•	•			•	•	•	•				•						
	EF11	Undervoltage release	•	C20	70	•			•	•	•			•	•	•	•				•						EF12
	4797		•	J L	70	•	•											•	•		•	•					
	4710	Cross & along versions	•	J	70	•												•							•		
	5017		•	J	70													•			•						

Cord connectors

Connector type	Extras	Connector type				Design				Approvals											
		Plug	Connector	IEC type	Max. pin temperature [°C]	Straight	Angled	Max. wire size [mm ²]	Max. wire size [AWG]	Max. cable dia. [mm]	VDE	ENEC	UR	cUR	UL	cUL	CSA	CSAus	CCC	PSE	Australia
REWIREABLE CORD CONNECTORS IEC 10 A / UL 15 A																					
	4732			E 70			1	18	8.5												
	4733			E 70			1	18	8.5												
	4735			E 70			1.5	14	10.0												
	4736			E 70			1.5	14	10.0												
	9009			E 70			1.5	8	10.0												
	P685			E 70			1	18	8.5												
	4782			C13 70			1	18	8.5												
	4785			C13 70			1	18	8.5												
	4300-06			C13 70			1	18	8.5												
	4762	IP 67	new	Spez			1.5	14	10.0												
	4781			C15 120			1	18	8.5												
	4784			C15 120			1	18	8.5												
	0102			C15A 155			1	16	10.0												
	0102-G	With gold plated contacts		C15A 155			1	16	10.0												
	0112			C15A 155			1	16	10.0												
REWIREABLE CORD CONNECTORS IEC 16 A / UL 20 A																					
	4796			I 70			1.5	14	10.0												
	4789			I 70			1.5	16	8.7												
	4300.0922			I 70			2.5	12	12.0												
	4795			C19 70			1.5	14	10.0												
	4790			C19 70			1.5	16	8.7												
	0104U			C19 70			2.5	12	13.0												
	4300.0921			C19 70			2.5	12	12.0												
	1658		new	C21 155			1.5	10	16.0												
	1659		new	C21 155			1.5	10	16.0												

Distribution units

					Approvals					
					ENIEC	UR	cUR	CSA	CCC	TUV
Connector type	Power input	Outlets	Number of outlets							
DISTRIBUTION UNITS 10 A / UL 15 A										
	0712	Appliance inlet C14	Appliance outlet type F	1		•	•	•	•	•
	4741	Appliance inlet C14	Appliance outlet type F	2						
	0909	Solder terminals	Appliance outlet type F	2 up to 7	•	•	•			
	4752	Quick connect or solder terminals	Appliance outlet type F	4	•	•	•			
	4754	Quick connect or solder terminals	Appliance outlet type F	4	Space for another element C14	•	•	•	•	
	4758	Quick connect or solder terminals	Appliance outlet type F	4	Space for a 62xx inlet with fuse	•	•	•		
	4747	Appliance inlet C14	Appliance outlet type F	4		•	•	•		
	4748	Power supply cord	Appliance outlet type F	4	Different main plugs available					
	4740	Appliance inlet C14 or power supply cord	Appliance outlet type F	5 or 6	Optional: switch, fuseholder or linefilter					
	FLBB	Power supply cord	EU/CH socket outlets	5	With line-filter and line-switch					
DISTRIBUTION UNITS 16 A / UL 16 A										
	4730	Appliance inlet C20	Appliance outlet type J	1	Plug coupler	•	•			•

Web Information

At schurter.com you can enter the connector type (e.g. 6610) into the search box and download the data sheets containing all relevant details.

Customized solutions

In addition to its broad product range, SCHURTER also offers individual services to fulfill all customer requirements.

We will build specific samples and provide you with your customized solution. schurter.com/connectors